

Racing 4T SAE 20W-50

DESCRIPTION

Racing 4T SAE 20W-50 is a high-performance engine oil which is formulated according to the latest technology. Selected base oils and a high additive content guarantee optimum lubrication under extreme running conditions.

PROPERTIES

- universal application
- high lubricant-film stability and excellent wear protection
- high shear and ageing stability
- outstanding cleaning and dispersion properties
- prevents black sludge
- low evaporation loss and oil consumption
- miscible with all commercially available engine oils
- suitable for wet clutches
- tested for compatibility with catalytic converters

classifications and specifications:

API SG/SJ/SL

TECHNICAL DATA

Viscosity class	: 20W-50
Density at 15 °C	: 0.89 g/cm ³
Viscosity at 40 °C	: 150 mm ² /s
Viscosity at 100°C	: 17.5 mm ² /s
Viscosity index	: 128
Flash point	: 240 °C
Pour point	: -28 °C
ASTM colour	: 3.5

APPLICATION

Four-stroke motorbike engines.

INSTRUCTIONS

The operating instructions of the engine manufacturer must be followed.

AVAILABLE PACK SIZE

Racing 4T 20W-50	1 l	Part no. 1500 D-GB-I-E-P
	1 l	Part no. 2656 D-PL-H-RO-TR
	1 l	Part no. 2762 D-NL-F-GR-ARAB
	5 l	Part no. 1501 D-GB-I-E-P
	20 l	Part no. 1560
	60 l	Part no. 1561

PI 08/05/12

Our information is based on thorough research and may be considered reliable, although not legally binding.

